

SEL-PLEX® PREMIX (600 ppm)

Selenium yeast for use in formulating complete feeds for pigs, chickens, turkeys and cattle
For use in free-choice salt mineral mixtures and feed supplements for limit feeding for beef cattle

Directions for use in livestock complete feeds

| |
|--|
| Pounds of Sel-Plex Premix to add per ton of complete animal feed (0.30 ppm of added selenium) |
| 1.0 lb per ton |

Directions for use in free-choice salt mineral mixtures for beef cattle

| | |
|--|--|
| To formulate salt mineral mixtures containing: | Pounds of SEL-PLEX PREMIX (600 ppm) to add per ton |
| Beef cattle – 13.6 mg Se/lb (30 ppm); provides the maximum allowed 3.0 mg/head/day at 3.5 ounces of daily intake | 100 lbs/ton |

Directions for use in supplements for limit-feeding for beef cattle

| Pounds of SEL-PLEX PREMIX (600 ppm) to add per ton of limit-fed feed | Added Selenium Concentration (ppm) | Daily Feed Intake (lbs) to provide the maximum allowed 3 mg of Se/head/day for beef cattle |
|--|---------------------------------------|--|
| 1.00 | 0.3 | 22.0 |
| 2.00 | 0.6 | 11.0 |
| 3.33 | 1.0 | 6.6 |
| 5.00 | 1.5 | 4.4 |
| 6.67 | 2.0 | 3.3 |
| 22.0 | 6.6 | 1.0 |

Guaranteed Analysis

| | |
|------------------|--|
| Total Selenium | Min. 595 ppm (mg/kg) – Max. 600 ppm (mg/kg) (Min. 270 mg Se/lb – Max. 272 mg Se/lb) |
| Organic Selenium | Min. 588 ppm |

Ingredients

Calcium carbonate, Selenium yeast, Brewers dried yeast and Corn distillers dried grains.

Caution: Follow label directions. The addition to feed of higher levels of this premix containing selenium is not permitted.

Warning: Selenium is potentially damaging to health. Use only in accordance with label directions and employ all protective measures indicated in the MATERIAL SAFETY DATA SHEET.

MATERIAL SAFETY DATA SHEET IS AVAILABLE FROM THE MANUFACTURER.

Net Weight: 55.1 lbs (25 kg) Item Number: 09.1418.067.022
USA.36

REV 04/12 JN

Manufactured by:

Alltech, Inc. • 3031 Catnip Hill Pike • Nicholasville, Kentucky 40356-8700 • USA • Tel: +1 (859) 885-9613 • Fax: +1 (859) 885-6736 • www.alltech.com
Variation in color does not affect product performance

